



AUTOMATIC TRANSFER SWITCH UNIT

PAC 17 | PAC 28
PAC 42 | PAC 70

FEATURES

- Four pole contactor
- Large space for the connection
- Fixing to wall
- Key selector for change-over manual control
- Meets EC directives

STANDARD EQUIPMENT

- IP 55 metal case painted with epoxy power
- Protection fuses
- Auxiliary terminal board
- selector for change-over manual control
- Indicator lights for mains or generator side
- Complete with fixing wall brackets



TECHNICAL DATA

	PAC 17	PAC 28	PAC 42	PAC 70
3 phase 400V power max.	17 kVA	28 kVA	42 kVA	69 kVA
3 phase 230V power max.	10 kVA	16 kVA	24 kVA	40 kVA
lth. rated current (E35 °C)	25A	40A	60A	100A
Working frequency	50 o 60 Hz	50 o 60 Hz	50 o 60 Hz	50 o 60 Hz
Icw - Short-circuit withstand current (1 sec.)	/	/	/	/
Dimensions h x w x d (mm)	500 x 400 x 200	500 x 400 x 200	500 x 400 x 200	500 x 400 x 200
Weight	25 Kg	26 Kg	27 Kg	29 Kg
IP protection degree	IP 55	IP 55	IP 55	IP 55
Fixing	Wall	Wall	Wall	Wall

GENERAL INFORMATION

COMPLIANCE GENERATING SETS WITH EC DIRECTIVES AND STANDARDS

2006/42 / EC (Machines Directive)
2014/35 / EU (Low Voltage Directive)
2014/30 / EU (EMC Directive)
2000/14 / EC (Directive Acoustic Emission for machines for use outdoors)
ISO 8528 (Reciprocating internal combustion engine driven alternating current generating sets)



ISO 9001:2008 - Cert. 0192

WARRANTY

All devices are covered by the manufacturer's warranty.

The company reserves the right to change this specification without notice. For further information please contact the sales department.

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy - phone +39-0290352.1 - fax + 39-0290390466 E-mail: info@mosa.it Web site: www.mosa.it

