

MOSA

Switch the power on

INVERTER



POWER AT YOUR FINGERTIPS



Silenced



Light



Electronic
devices



GE 2000 MI



Air cooling



petrol



single-phase power



Manual recoil

- Automatic voltage regulation
- Engine stop due to low oil level
- ESC (Engine Speed Control) function
- Overload protection
- Battery charger with thermal protection
- Parallel output with a second generator
- N ° 2 USB ports

ALTERNATOR:

Permanent magnet	
Stand-by single-phase power	2 kW / 230 V / 8.7 A
PRP single-phase power	1.8 kW / 230 V / 7.8 A

ENGINE:

GK 80-i	
Tank capacity	5 lt
Running time (75% to PRP)	5.3 h

GENERAL SPECIFICATIONS:

Sockets	1x230V 16A 2P+T Schuko
Dimensions (L x W x H)	498 x 298 x 459 mm
Dry weight	22 kg
Measured acoustic power LwA	90.5 dB(A) (65.5 dB(A) @ 7m)
Guaranteed acoustic power LwA	92 dB(A) (67 dB(A) @ 7m)

GE 4000 MI

ALTERNATOR:

Permanent magnet	
Stand-by single-phase power	4 kW / 230 V / 17.4 A
PRP single-phase power	3.6 kW / 230 V / 15.6 A

ENGINE:

GK 80-i	
Tank capacity	12 lt
Running time (75% to PRP)	8.5 h

GENERAL SPECIFICATIONS:

Sockets	2x230V 16° 2P+T Schuko
Dimensions (L x W x H)	605x432x500mm
Dry weight	42 kg
Measured acoustic power LwA	91.8 dB(A) (66.8 dB(A) @ 7m)
Guaranteed acoustic power LwA	92 dB(A) (67 dB(A) @ 7m)



Air cooling



petrol



single-phase power



Manual recoil



electric starter

- Automatic voltage regulation
- Engine stop due to low oil level
- ESC (Engine Speed Control) function
- Overload protection
- Battery charger with thermal protection
- Parallel output with a second generator
- N ° 2 USB ports
- Manual towing trolley with retractable handle